



2021.05





















NICRON LIGHTING CO.,LTD.

ADD: 202, Building 25, Vanke Jinyu Binjiang Plaza, 13 DeSheng Middle Road, Daliang, Shunde District, Foshan City, Guangdong Provience, China POSTCODE: 528333

Tel: +86-757-2232 8481 Fax: +86-757-2232 0377 Email: martin.wu@nicronlight.com Service: info@nicronlight.com



Professional Industry Lighting Manufacturer



About **NICRON**®

NICRON is an innovative and independent brand found in Shunde, Foshan, Guangdong, China in 1999. It belonged to Aoneng Lighting Co.,Ltd. But from 2021 April, for futher development, NICRON seperated from Aoneng and become an indepent company. NICRON is professional in developing new-style portable illumination products according to customers' requirements, products of NICRON cover LED flashlights, Head lamps, Work lights, Lanterns, Bike flashlight, etc.

The concept of NICRON is to provide portable lighting tools with high quality and reliability to customers around the world. Now, our products have been sold to many countries, such as Japan, Korea, France, Denmark, Thailand, Malaysia, Russia, and Ukraine.

NICRON — Safe and Reliable Portable Lighting Tools.

We are looking forward to work and create a bright future with you.

Factory Pictures







Workshop Office

Assembly Workshop

CNC Lathe







Hardware Workshop

Testing Lab

Laser Etching



Contents

1.	Brand Concept & Technology Intruduction	3
2.	Application Range	5
3.	Product Recommend	7
4.	High Performance Flashlight Series	9
5.	90° Twist Flashlight Series (Bendable)	13
6.	Slim Work light	16
7.	Zoomable Flashlight Series	17
8.	Key-Chain Flashlight Series	19
9.	Pen Light Series	20
10.	Anti-Explosion Series	21
11.	Headlamp Series	23
12.	The Belt and Road Economic Product Series	25
13.	Accessories and Display Shelf	29
14.	Package Pic. and Sales-box	31
15.	Parameter Sheet	33

01 About NICRON Contents 02







Brand Concept:

★To provide portable lighting tools with high quality and reliability to customers around the world.

Brand Goal:

★To become a lead company in lighting field and to enhance ability to meet customers' requirements.

Brand Plan:

- ★Be a high-end brand: positioned as a high-end brand in portable lighting field, and become a leading brand in 90° Angle Twist multi-function flashlight in 3 to 5 years.
- ★Upholding "customer-centered" concept: to have an overall understanding of customer's demands and to be devoted to creating value for customers.
- ★Excellent operation: to continue optimization, fix process, improve efficiency of management and meet customers' needs repidly.

Brand Value:

★ Honesty, Responsibility, Innovation, Openness

Brand Culture:

★To be consumers' demands oriented, be a striver, to focus on better performance and keep improving.

Main Technology

- ★ Strong aluminum alloy body, good quality anodizing finish to protect surface.
- ★ Fashion and unique design contribute to increase brand recognition.
- ★ Special heat sinking system keep the light reliable.
- ★ Professional lens and reflector with good luminous efficiency.
- ★ High-efficiency PCB, easy-to-operate and smart switch design.

Excellent luminous experience

- ★ High volume rechargeable battery with protection system to provide safe and super long run time.
- ★ Professional lighting system comfortable light beam.
- ★ Multi-modes design satisfies demands for different usage and scenarios.
- ★ Smart setting design (hidden, max, strobe, SOS) with good and easy operate feeling.
- ★ Max up to IP68 dust and waterproof, work 2m below water; normally IP65 dust and rain resistant, build for various environment.
- ★ Standard work temperature: -20°C~50°C.
- ★ Max drop resistant 1~2 meter.

Flashlight Component



ANSI/NEMA FL 1-2009 Icon introduction









































Automotive maintains

Suited flashlight with long work time, stable performance, skid resistant and hands-free design with magnet, suitable for automotive maintains.

B75, B73, H10R, H30F, F81, F72, B22, WL15R, H15, H35, H17

Factory and machine repairs

Need simple function but good drop resistant, can hands-free work, corrosion resistance, water and oil resistant, long run time.

B400, B200, B60, H10R, WL15, WL81, N61, N63, H40



Electric power & Communication rush repairs

Suited flashlight with high luminance, long light distance and work time, water and dust resistant with signal light. Stable and safe flashlight suitable for using in extreme environment.

B200, B60, B62, B24, H30, B70, B71, WL15, WL81, H15, H35

Constructional engineering

Require super light distance, hands-free for work with longer run time and high drop resistant.

B400, B200, B60, F81, B74, B73, B24, H30, WL81, H35, H17





Railway works and repairs

Suited flashlight with far light distance, long-lasting work time and hands-free design with magnet.


B200, B400, B60, B62, B24, F81, H30, WL81, H15, H35, H17

Ship industry

Require water proof, seawater resistant, longer run time, with magnet for hands-free work.

B400, B200, B60, B24, F81, H30, WL81, H15, H35, H17





Anti-explosion proof lights

Base on China standard, limit to use in the air environment district 1, district 2, and II A, II B, II C grade anti-explosion proof air environment. Usually apply to electricity, metallurgy, petroleum, chemical engineering, industrial and mining, fire control etc. combustible and explosive area.

EXB701, EXB90, EXB93, EXH90, EXB91, EXB95

Aviation industry

Require super brightness, long light distance, easy to carry, multi-functions and signal lamp

B400, B200, B60, B24, F81, H30, WL81, H15, H35, H17





Home improvement and DIY


Require portable, simple function, hands-free for work, easy to keep and take in.

B10, B74, B73, N1, N4, N5, N61, N63, H15, H17

EDC-every day carry & Gift

Require light weight, small size, easy to work.

B10, N1, N1.1, K15 B24, B74 Pro - - Gift



05 Application Range

536 M 1000 LM

12000 LM





950 LM





1000 LM

1000 LM



150 LM

Product Recommend



300 LM

B200 IP68 Long Beam Distance

Tactical Flashlight

B400 IP67 Crazy Bright Tactical Flashlight

B11 IP67 Mini Rechargeable Tactical Flashlight

B74 Pro IP65 Mini Rechargeable

700 LM

B71 IP67 Rechargeable Twist Flashlight Twish Flashlight

B75 IP65 Rechageable Twist Flashlight with UV

Head Lamp

B73

MAGNET

IP65 Magnet Rechargeable Twist Flashlight

100 LM

WL15R IP64 Rechargeable Work Light

1000 LM



600 LM



Zoom Flashlight

F81 F51 IP65 **IP65** Zoomable Pocket Zoomable Rechargeable Flashlight Rechargeable Flashlight

140 LM

F72

IP65

Zoomable

Pen Light



MAGNET

Pen Light **B24**

IP65 Rechargeable Pen Light with Laser

500 LM



Dual-fuel

IP65 Magnet Tail Assembly Headlamp

1000 LM



PCEC EX

Anti-Explosion **EXB701**

Anti-Explosion Twist Rechargeable Flashlight

120 LM

H11

IP65 Twin-Engines Rechargeable Headlamp

H35

High Performance Flashlight Series

These products are designed for professional lighting purposes. Can be used for test, machine repair, security. With high performance, long operate time, good water -proof, suitable for complicated and extreme environment.





B400

Crazy Bright Tactical Flashlight 116W







Wide-angle beam design, high-class flashlight. Suitable for searching ,security, photography, industry lighting.














Please place the battery as the sticker shows



4*18650 Li-ion Battery, 3000mAh

Gift-box, 0/6 per carton, Flashlight, Battery, DC-charger, Car-charger, Packbag

426g (without batteries) 152mm × 64mm × 56mm





& Photography tripod

Application



28° Beam Angle

Railway repair



Construction site



Crazy Bright




Search & Rescue


B200

Long Beam Distance Tactical Flashlight 9W





With 536 beam distance, 1000 lumens, and good waterproof.





ANSI/FL1	Low	Med	High	Strobe	sos		
와설 Brightness	100	300	1000	1000	1000		
(Run Time	12H	3.5H	3H	1	1		
LED	CREEX	P-L HI V2	2				
Battery	2*18650 Full char	Li-ion Ba ged time	attery, 26 6 hrs, 30	00mAh 0times			
Weight Weight	370g (wi	370g (without batteries)					
Erren Size	Length 235mm × Max dia 59mm × Dia31mm						
Package	PVC-Co Battery*	olor Box, 2, Micro	5/10 per -USB Ca	carton; Fl ble	ashlight,		





/olume Indi	cator			
100%		10%	20%	10%
	III II	III II		

Reptagnable USB Cable EDC Tactical

Mini Rechargeable Tactical Flashlight 9W

B11

With good water resistance, high brightness, Smart double switch to change any mode. Suitable for EDC, industry, or outdoor work, etc.







ANSI/FL1	Low	Med	High	Max	Strobe	SOS	
⊋¹½ Brightness	70	160	300	950	950	950	
(Run Time	7H	3H	2H	1.5H	1	1	
LED .	CREE	CREE XP-L HI V2					
Battery		18350 Li-ion Battery, 1100mAh Full charged time 4 hrs, 300times					
Weight Weight	80g (w	80g (without batteries)					
Size	Length 80mm × Max dia 28mm						
Package		color box			on, Flash	nlight,	



B60

1000_{LM}

35н

High performance flashlight 10W

With good waterproof, high brightness, long beam distance. Suitable for Electronic repair, Railway repair, ect.




Charging indicator





А	NSI/FL1	Low	Med	High	Max	Strobe	sos
314	Brightness	50	140	450	1000	1000	1000
(1)	Run Time	35H	15H	5H	4H	1	-1
*	LED	CREE	XP-L H	IV2			
1	Battery	18650 Full cha	Li-ion E arged tir	Battery, me 6 hrs	3400m/ s, 300tin	Ah nes	
4	Weight	166g (v	without I	batterie	s)		
ETTE	Size	Length	154mm	x Max	dia 41n	nm × Dia	a28mm
0	Package			x, 5/20 p -USB C		on, Flash	light,



Slim size, good waterproof, portable design, safe and reliable, long run time, suitable for EDC, industry and outdoor work, ect.

	E	36	2	
,	31/2 Brightness	Q	50	LM
	Q Run Time		60 _H	l
	170m	7200cd	IP67/1m	√ 1m



Charging indicator



Full Charged: LED turned off

ANSI/FL1	Lower	Low	Med	High	Max	Strobe	SOS
와일 Brightness	15	45	120	330	950	950	950
(Run Time	35H	35H	15H	5H	4H	1	1
LED	CREE	CREE XH-L HD V5					
Battery	18650 Full ch	18650 Li-ion Battery, 3600mAh Full charged time 6 hrs, 300times					
Weight Weight	80g (v	80g (without batteries)					
Size	Lengt	Length 128mm × Max dia 28mm × Dia26mm					
Package						, Flashli st strap	ght,



90° Twist Flashlight Series

NICRON adjustable head flashlight can free user's hands, wide angle lighting design, with UV light, or with red+green light, magnet tail to handle complex environment.





Scratch detect



Liquid detect




Protection detect, Bio-polymerization, Surface check, UV solidify, Criminal detect, Jewelry/Diamond /Ore Identification, Sensor test

B75


20н

Rechargeable Twist Flashlight with UV light 10W











ANSI/FLI	High	меа	Low	UV
کاند Brightness	1000	500	100	395nm
(Run Time	3H	4H	20H	7H
₩ LED	Samsung	LED, UV	-700mW/3	395nm
Battery	18650 Li- Full charg	ion Battery, ed time 6 hr	2600mAh s, 300times	3
Weight Weight	160g (with	out battery)	
Errer Size	Length 16	0mm × Max	x dia 28mm	
Package		ype-C Cab		Flashlight,

NICRON®

B70 Twist Flashlight with green light and red light 10W

light work for military, railway work, etc.

B70 is a twist rechargeable flashlight with excellent brightness, signal




















ANSI/FL1	Low	Med	High	Max	Strobe	sos
ئالا Brightness	10	80	500	1200	1200	1200
(Run Time	100H	15H	4.5H	4H	1	1
: LED	OSRAM LED					
Battery	18650 Full cha	Li-ion E arged tii	attery, and the factor of the	2600m/ , 300tir	\h nes	
Weight Weight	153g (without batteries)					
Errit Size	Length 160mm × Max dia 26mm					
Package			c, 5/20 p		n, Flash	ılight,

B71

Magnet Rechargeable Twist Flashlight 10W

1000 LM **100**н

B71 is a brand-new patented shaft product, the size is one-third smaller than B75, B70, waterproof grade is IP67, better than the old version, but only has white light





ANSI/FL1	Max	High	Mid	Low	Strobe	sos
عالم Brightness	1000	500	80	10	1000	1000
(Run Time	4H	5H	25H	100H	1	1
LED	Samsu	ng LED				
Battery	18650 Full cha	Li-ion E arged tii	attery, ne 6 hrs	2600m/ s, 300tir	Ah nes	
Weight Weight	153g (v	without I	oatterie	s)		
Frm Size	Length	126mm	× Max	dia 27n	nm	
Package	PVC-c Battery	olor bo	x, 5/20 p -C Cabl	er carto e	on, Flash	nlight,
^	PVC-c	olor box	x, 5/20 p	er carto		nlig

B73

90° Twist Pen light with Magnet 3W





B73 series is pen size angle flashlight, work for narrow place or mount on body easy for work like electric, automotive repairing etc., B73 is dual-fuel flashlight, standard package with 10840 innovation slim li-ion battery, and also can use 2AAA dry battery.







Al	NSI/FL1	High	Low	Strobe	sos	
Ē	Brightness	150	60	150	150	
	Run Time	2.5H	8H	1	1	
	Brightness	150	60	150	150	
	Run Time	35H	4H	1	1	
- 3	E LED	SAMSUNG	3			
F	Battery	1*10840 Li time 4hrs, 3	-ion Batte 300times)	ry(700mAh,o ; or 2*AAA	charge	
4	Weight 51g (without battery)					
Size Length152mm × Max dia18mm × Dia						
(Package	PVC-color (Battery)	box, 5/20	per carton, F	lashlight,	

Mini Rechargeable Twist Flashlight 7W





Dual-fuel

AA 14500Li-ion

B74 Pro

B74 is a mini size twist flashlight with 700lm brightness and 4 optional colors, work for Everyday carried, It is dual-fuel, standard package with 14500 or 1AA dry battery.



Α	NSI/FL1	Low	Med	High	Strobe	sos
	Brightness	100	250	700	700	700
7	Run Time	7H	2.5H	1H	1	1
۵	Brightness	10	30	100	100	100
	Run Time	35H	20H	4H	1	1
Ą	E LED	Samsun	g LED			
Î	Battery	14500 Li Full char	i-ion Batt	ery, 750 4 hrs, 30	mAh IOTimes	
Weight 56g(without battery)						
Length112mm × Max dia21mm × Dia18n						18mm
PVC-color box, 5/20 per carton, Flashlight Battery, Micro-USB Cable						hlight,

WL81

USB Rechargeable Slim work light





WL81 has an Extra work flood light at side, with strong magnet for hands-free work. Smart switch button with battery volume and charging status indicator, easy to work and change modes by single hand, Micro-USB rechargeable directly





Al	NSI/FL1	High	Med	Low	Strobe	sos
Spotlight	31/2 Brightness	1000	500	80	1000	1000
Spot	Run Time	3H	3.5H	10H	1	1
Floodlight	Brightness	500	1	35	1	1
Flood	Run Time	5H	1	19H	1	1
3	: LED	SAMSU	NG			
F	Battery	1*18650 time 4hr		attery(2	600mAh),	charge
4	Weight	69g (with	out batte	ery)		
ETT	Size	Length1	21mm ×	Max dia	29 mm	
	Package	PVC-co (Battery)		/20 per d	carton, Fla	shlight,

WL15R

Portable Rechargeable Work Light 5W





314 Brightness	300 LM		
Q Run Time		8 н	I
56m	800cd	IPX4	√ 1m

Magnet tail, Slim size work light rechargeable with Li-ion battery insert. Suitable for machine repair.



48					
	187973				
	High	Low			
rightness	200	80 _{COB}			
um time	2H	8H			
	High	Low			
rightbess	300	100			
un time	2H	5H			

المراج Brightness	200	80 _{COB}
Num time	2H	8H
	High	Low
کائد Brightbess	300	100
Nun time	2H	5H
* LED	SEOUL LED, COB	
Battery	10840 Li-ion Batter	ry Insert (700 mAh)
∆ Weight	80g, battery exclud	е
Size	Length164mm × Ma	x dia 22mm
Package	PVC Blister, 6pcs/b	ox, 48pcs/carton






Mini Zoomable Flashlight 7W

F51 is a dual-fuel mini size focus flashlight, work by 1AA alkaline battery or 14500 li-ion battery, li-ion battery can boost higher brightness, hands-free hat lamp, can stand uprightly as a candle light. work for many ranges.

600LM

F51



А	NSI/FL1	High	Med	Low
Ê	Brightness	600	250	100
	Run Time	1H	2.5H	5.5H
	Brightness	140	65	35
	Run Time	6H	2H	1H
3	: LED	CREE LED		
F	Battery	14500 Li-ion E Full charged ti	Battery, 750mAl me 4 hrs, 300Ti	h mes
Δ	Weight	55g(without ba	attery)	
E	Size	Length103mm	× Max dia26mm	n × Dia20mm
4	Package	PVC-color box	, 5/20 per cartor	n, Flashlight,



F81 Zoomable Rechargeable Flashlight 9W



F81 is a big size and high brightness rechargeable focus flashlight, type–C charging system, can easily be operated by single hand with one switch, push and pull to zoom by one hand. Suitable for industry, automotive,etc.






ANSI/FL1	Low	Med	High	Max	Strobe	sos
کائد Brightness	s 50 150 500 1000 100 1				150	
(Run Time	20H	7H	4H	2H	1	1
* LED	CREE XP-L V5					
Battery	18650 Li-ion Battery, 2600mAh Full charged time 6 hrs, 300times					
Weight	156g (v	without I	batterie	s)		
Erren Size	Length	163mm	× Max	dia 35n	nm × Dia	a26mm
Package			x, 5/20 p -USB C		n, Flash	nlight,



Zoomable Penlight 3W

F72 is an economic focus penlight, work by 2AAA alkaline battery, suitable for electrical industry, automotive industry, etc.







ANSI/FL1	High
్తి Brightness	140
(Run Time	2.5H
LED	SAMSUNG LED
Battery	2*AAA Battery
Weight Weight	41g (without battery)
Size	Length 144mm × Max dia 18mm
Package	PVC-Color Box, 5/20 per carton, Flashlight



Zoomable Flashlight Series

K15

Mini Bamboo Flashlight 1W









Bamboo design, Head switch key-chain flashlight







ANSI/FL1	High	Low	Strobe
≥4 Brightness	80	20	80
Run Time	2H	7H	1
LED	CREELED		
Battery	1*AAA Battery		
Weight	17g (without ba	attery)	
Size	Length 75mm	× Max dia 16m	ım
Package	PVC-color box		on,

Light Series

B10

Rechargeable key-chain flashlight 3W









ANSI/FL1	High	Med	Low	Strobe
ያነሩ Brightness	200	100	30	200
(Run Time	2H	4H	10H	1
LED	CREE XP	-E2 R3		
Battery	1*16340 Li Full Charge	i-ion Batter ed 4 hrs, 30	y(650mAh) 0times	
Weight	60g (withou	ut battery)		
Erren Size		mm × Max o		
Package		r box, 6/36 p Keychain, l	er carton, Battery, USI	3 cable



ANSI/FL1	High	Med	Low	Strobe
과생 Brightness	200	100	30	200
(Run Time	2H	4H	10H	1
LED	CREE XP	-E2 R3		
Battery	1*16340 Li Full Charge	-ion Batter ed 4 hrs, 30	y(650mAh) Otimes	,
Weight Weight	60g (withou	ut battery)		
Erren Size	Length 65r	nm × Max d	lia 20mm	
(S)	PVC-color	box, 6/36 p	er carton,	



N1.1

10 LM

Tiny flashlight 0.25W







Head switch

ANSI/FL1	High		
강峰 Brightness	10		
(Run Time	1H		
LED .	CHINA 5mm LED		
Battery	4*LR41 Battery		
Weight	4.2g (without battery)		
Size	Length 36mm × Max dia 11mm		
Package	PVC-Blister, 12/120 per carton, Flashlight, Keychain, Battery		

EDC Patent

150 1.5H LIUMILEDS 10840 Li-ion Battery 60g (without battery) Length 151mm × Max dia 28mm PVC-color box, 5/20 per carton, Flashlight

Class 3A Laser

Wavelength 650nm Avoid direct eye exposure

Rechargeable penlight with laser 1W

B24 is professional indicated flashlight, red laser up to 100 meter distance, It works for illumination and communication between workers, can make eveything understand well when work, it is suitable for construction, electrial, ship industry, aviation range, etc.



B24



3 modes and laser guiding.





High CRI zoom flashlight 1W

Simulated sunlight(CRI 95) for color match.





ANSI/FL1	High
Brightness کائے	120
(Run Time	2H
: LED	LIUMILEDS
Battery	2*AAA Battery
Weight	41g (without battery)
Size	Length 144mm × Max dia 18mm
Package	PVC-Color Box, 5/20 per carton, Flashlight



NICRON Anti-Explosion series certified by China National Quality Assurance Authority with good anti-explosion performance, can work at combustible and explosive site.

Limited to use in the air environment District1, District2 and IIA/ IIB /IIC

EXB701

Anti-Explosion Twist Flashlight



EXB701 is a rechargeable Explosion-proof Bendable Flashlight with red and green signature lamp.





PCEC EX



ANSI/FL1	Low	High		Strobe
کائد Brightness	30	100		100
Rum time	40H		12H	1
Explosion Sign	Exib CT4 C	3b		
Applicable Temperature	-20°C ~ +45°C	С	Application	1 Division 2 Division
Rated Power	1W - 3W		Rated Voltage	3.7V
Relative Humidity	≤95%RH(25	℃)		
LED	CREELED			
Battery	1*18650 Li-ion Battery (2600mAh) Charge time ≤ 6H, 1000times			
Weight	153g(without battery)			
French Size	160mm × 28mm			
Package	PVC-color box Battery, Micro			

Only For Aisa





ANSI/FL1	Low	High		Strobe	
₃ Brightness	60	200		200	
Rum time	20H	8H		1	
Explosion Sign	Fxib CT4 Gb				
Applicable Temperature	-20℃ ~ +45℃	Application		1 Division 2 Division	
Rated Power	1W - 3W	Rated Voltage		3.7V	
Relative Humidity	≤95%RH(25℃)				
LED	CREE XP-E2	R3 LI	ED		
Battery	1*18650Li-ion Battery (2200mAh) Charge time ≤8H, 1000times				
Weight	175g(without battery)				
Error Size	Length160mm × Max dia35mm × Dia28mm				
Package	Color Box, 5/20pcs per Carton, Flashlight Battery, DC-charger				

Slim Anti-Explosion Flashlight

Suitable for gas station, petrochemical industry, chemical industry,



EXB90










ANSI/FL1	Low	High		Strobe	
ያነፉ Brightness	80	- :	250	250	
(Rum time	16H		8H	1	
Explosion Sign	Exib CT4 Gt)			
Applicable Temperature	-20°C ~ +45°C		Application	1 Division 2 Division	
Rated Power	1W - 3W	Rated Voltage		3.7V	
Relative Humidity	≤95%RH(25°C)				
LED	CREE XP-G2	R5 LI	ED		
Battery	1*18650Li-ion Battery (2200mAh, inset) Charge time ≤8H, 1000times				
Weight	215g(Built-in battery)				
Size	Length192mm × Max dia52mm				
Package	Color Box, 5/2 Battery, DC-c			n, Flashlight	

Compact Anti-Explosion Flashlight








EXB93







Anti-Explosion Headlamp





ANSI/FL1	Low	High		Strobe
ያካሬ Brightness	48	170		170
Num time	16H		8H	1
Explosion Sign	Exib CT40	3b		
Applicable Temperature	-20℃ ~+45℃	С	Application	1 Division 2 Division
Rated Power	1W - 3W Rated Voltage		3.7V	
Relative Humidity	≤95%RH(25	°C)		
₩ LED	CREE XP-E	2 R3	LED	
Battery	1*Li-ion Battery (1600mAh, inset) Charge time ≤ 8H, 1000times			n, inset) nes
Weight Weight	88g(Built-in battery)			
Size	Length60mm × Width51mm × Height50mm			
Package	Color Box, 5/20p Battery, DC-cha			



	ΧI		9	U	
312 Brightness	1	7() _L	M	

EVIJOO








EXB91

Miniature explosion-proof working flashlight





Battery cabin at back side, keep the balance of beam distance and run time, with safety belt that can keep the position.







Type-C USB direct charge



ANSI/FL1	Low	High	Strobe		
పోడ Brightness	100	270	270		
Run time	8H	4H	1		
Explosion-proof mark	Exib II CT4 Gb				
Working temperature	-20℃ ~ +45	°C Applicable	area Zone1、2		
Rated power	r 1W - 3W Rate		age 3.7V		
Relative humidity	≤95%RH(A	mbient temp	perature25℃)		
* LED	CREE LED				
Battery	1*18650 rechargeable battery, 1900 mAh, Charging time ≤ 8H				
₩ Weight	91g, exclude battery				
Size	123mm × 23mm				
Package	Color box, 5/3 Battery, USB				



PCEC EX

EXB95

1000 LM

16

Portable explosion-proof searchlight EXB701 is an L-corner explosion-proof working lantern with

white, red and green light







ANSI/FL1	Low	High	Strobe		
۳۴ Brightness	200	1000	1000		
Run time	16H	8H	1		
Explosion-proof mark	Exib II CT4 G	ib			
Working temperature	-20℃ ~+45℃	Applicable a	rea Zone1、2		
Rated power	1W - 3W	Rated voltag	ge 3.7V		
Relative humidity	≤95%RH(Ambient temperature25℃)				
* LED	3*CREE LED				
Battery	1*18650 rechargeable battery, 2600 mAh, Charging time ≤ 10H				
₩ Weight	882g, exclude battery				
Size	187mm × 123mm × 68mm				
Package	Color box, 5/20 per carton, Flashlight Battery, USB cable, Flashlight Sleeve				

Headlamp Series

Nicron portable heaplamp has delicate appearance, reliable functions and high quality of waterproof. Suitable for Industry lighting and maintenance.




Twin Engines Rechargeable Aluminum Headlamp

H17

Type C USB rechargeable Headlamp, with Flood light good for long time work and can protect eyes





ANSI/FL1	Low	Med	High		
کاند Brightness	30	150	500		
Run Time	13H	3H	1.5H		
LED .	COB				
Battery	14500 Li-ion Battery, 800mAh Full charged time 6 hrs, 300times				
Weight	42g (without batteries)				
Region Size	65mm × 34mm × 35mm				
Package	PVC-color box, 5/20 per carton, Headlamp, Battery, TypeC Cable, Headband				





Type-C Charger with indicato

Twin-Engines Mini Rechargeable Aluminium Headlamp

H11

H11 is a handlamp with high-end aluminium alloy body, good quality anodizing coating, type-C rechargeable Headlamp.





23 Headlamp Series Headlamp Series 24 H35

Twin Engines Rechargeable Aluminum Headlamp



1600_{LM}

TYPE C rechargeable directly, Anti-slip belt can be mounted on helmet directly. Standard package include 18650 li-ion battery, suitable for hands-free work, inspection, fishing.








Α	NSI/FL1	Super bright	High	Middle	Low	
ight	와설 Brightness	1600	500	250	50	
Spotlight	Nun Time	2	3	6	30	
loodlight	عادي Brightness	800	400	200	50	
Flood	(Run Time	2	3	6	30	
	LED	Samsung LE	D			
	Battery	18650 Li-ion Battery, 2600mAh Full charged time 6 hrs, 300times				
	Weight	58.5g (without batteries)				
	Erren Size	75mm × 41mm × 43mm				
	Package		PVC-color box, 5/20 per carton, Headlamp, Battery, Type-C Cable, Headband			



Rechargeable Tactical Headlamp 9W

H30

900_{LM} 100_H T





ANSI/FL1	Lower	Low	Med	High	Max	Strobe	sos
少化 Brightness	15	70	130	350	900	900	900
Run Time	100H	35H	13H	5.5H	5H	1	1
: LED	CREE	CREE XM-L2 U2					
Battery	18650 Full ch	18650 Li-ion Battery, 3400mAh Full charged time 6 hrs, 300times					
Weight Weight	180g	180g (without batteries)					
Size	78mm × 46mm × 44mm						
Package		PVC-color box, 0/10 per carton, Headlamp, Battery, Micro-USB Cable, Headband, Helmet Holder					






H₁₀R

450 LM

Mini Inovational Headlamp 5W







Magnet Tail	D\/
	TU
Portable	N. A.

sos 450

150

A	NSI/FL1	High	Low	Str
Ē	Brightness	450	120	45
	Run Time	1.5H	3.5H	-
	Brightness	150	35	15
	Run Time	2H	6H	1
3	: LED	Samsung LED		
₽ Battery		14500 Li-ion Battery, 750n Full charged time 4 hrs.		
4	Weight	65g(without battery)		
65	Size	Length 93n	nm × Max o	liaB21



Rechargeable Zoomable Headlamp 9W

Battery cabin at back side, keep the balance between beam distance and run time. With safety belt to keep the position.







ANSI/FL1	High	Med	Low	Strobe	SOS			
الله Brightness	900	450	200	900	900			
(Run Time	2H	2.5H	5.5H	1	1			
LED .	CREEX	CREE XM-L2 U2						
Battery		18650 Li-ion Battery, 3400mAh Full charged time 6 hrs, 300times						
Weight	195g (without batteries)							
Size	78mm × 50mm × 44mm							
Package		PVC-color box, 0/10 per carton, Headlamp, Battery, Micro-USB Cable, Headband, Helmet holder						





Charging turn red Charged turn green

Dual-battery

25 Industry Flashlight Series

N4

Slim Aluminium Flashlight

Smart switch, easy to work and change modes by single hand

250 LM





N4	High	Low	Strobe			
Brightness 250		80	250			
Nun Time	4H	10H	1			
Package	Package PVC-color box, 5/20 per carton, Flashlight					
: LED	Beam Distance	Intensity	F Battery			
CREE XP-G2 S2	140m	5000cd	2*AAA Battery			
Water resistance	Drop resistance	Weight Weight	rental Size			
IP65	1m	72g	L155mm × Dia26m			

N5

Compact USB Rechargebale Flashlight

300 LM

3*AAA Batter

Small	and	exquisite	appearance	design,	easy to	carry	and	suitable	for	night	ride



N5	High	Low	Strobe			
کاند Brightness	200	25	200			
Run Time	4H	13H	1			
Package	PVC-color box, 5/20 per carton, Flashlight					
LED	Beam Distance	Intensity	Battery			
CREE XP-G2R3	178m	7800cd	3*AAA Battery			
Water resistance	Drop resistance	Weight	rrrr Size			
IP65	1m	85g	L114mm × Dia30mm			

N1

1AAA Mini Keychain Flashlight



Patent design, mini size good for EDC



N1	High					
Brightness عالم	20					
Nun Time	10H					
Package	PVC-color box, 6/36per carton, Flashlight					
: LED	Beam Distance	Intensity	F i Battery			
China LED	24m	144cd	1*AAA Battery			
Water resistance	Drop resistance	Weight Weight	rent Size			
IP65	1m	18g	L72mm × Dia16mm			

N61/N63 Economic rechargeable flashlight 3W



N61

Classic rechargeable EDC Flashlight/Classic long beam distance flashlight Rechargeable 18650 battery, can be used for industry lighting





N61	High	Low	Strobe			
عالم Brightness	300	60	300			
Nun Time	4H 16H /					
LED .	CREE XP-G2 S2					
Battery Battery	1*18650 Li-ion Battery, 2000mAh, Charge time 5 hrs, 300 times					
Weight	113g (without battery)					
Size	Length126mm × Max dia30mm × Dia26mm					
Package	PVC-color box, 5/20 per carton, Flashlight, Battery, USB-cable, twist strap					

N63	High	Low	Strobe						
عاد Brightness	300	70	300						
(Run Time	4H	16H	1						
LED	CREE XP-G2	2 S2							
Battery	1*18650 Li-ion Battery, 2000mAh, Charge time 5 hrs, 300 times								
Weight	166g (without battery)								
Erren Size	Length147mm × Max dia47mm × Dia26mm								
Package		PVC-color box, 5/20 per carton, Flashlight, Battery, USB-cable, twist strap							



Charging turn red	Charged turn gree

Suitable for electric repair, railway repair.

H40 Portable plastic headlamp 3W







ANSI/FL1	High	Low			
Brightness عالم	200	45			
(Run Time	4H	18H			
ED LED	CREE XP-G2 S2				
Battery	3*AAA Battery				
Weight	125g (without battery)				
Errer Size	80mm × 40mm × 35mm				
Package	PVC bubble wrap, 6/24 per carton, Headlamp				

27 Industry Flashlight Series

High Capacity USB Charge Li-ion Battery

Low cost and environmentally friendly

The 18650 Li-ion battery can be recharged over 300 times, equal to 1000 pairs of AA batteries or 300 pairs

of CR123A batteries. 1000 pairs 1.5V AA battery 300 pairs 3V CR123A 3.6V 18650 Li-ion



- ★ Microporous barrier protects delicate internal components.
- ★ Pressure relief valve activates in the event of a rapid temperature increase.

Battery volume: 2600mAh

Nominal voltage: 3.7V

★ Built-in PTC inhibit high current surges.

★ 3400mAh 18650 Li-ion rechargeable battery.

- ★ Innovative anode design with high temperature resistance.
- ★ Automatically protects against overcharge, over discharge and short-circuiting.



Battery volume: 750mAh Nominal voltage: 3.7V

Battery volume: 600mAh Nominal voltage: 3.7V

区区

Red: Charging

Battery volume: 650mAh Nominal voltage: 3.7V

Green: Full Charged

Display Shelf

S21



Hardware Ground Display Shelf

S20

Size: 700*300*1650mm





Display shelf on show or shop in same way

Charger

Battery volume: 3400mAh

Nominal voltage: 3.7V



USB-10 **USB** charger plug

*Fit to all standard USB cable



NLR-1000 Multi-function Li-ion charger

*Can discharge the li-ion battery to mobile phone *Used for 10440~26650 size li-ion rechargeable battery *Smart USB charge and discharge control system

Apply to these Batteries 16340 10440 14500 18650 26650





Warranty Terms

A. 2-year free repair: NICRON will repair a light free of charge within 2 years (non-detachable light: 1 year, rechargeable battery and other accessories: 0.5 year) of purchase if problems develop with normal use.

Product Category	Free Warranty Lead Time
Flashlight, Headlamp, Worklight	24 mouths
Accessories / Charger, Battery, etc.	6 mouths

- B. Lifetime maintenance: Customers of NICRON enjoy a lifetime maintenance. However, repair fee will be charged for purchase 2 years ago. The total repair fee will be depended on the component.
- C. Repair of man-made damages, such as using products incorrectly, will be charged for some material cost, labor cost remain free.
- D. For more details about warranty service, please contact local distributors, dealers, official hot line or send email to the following address: info@nicronlight.com, or call +86 757 2232 8481 / 4008 032 838.

English Package















H20



B70

B73







B24 B22

WL15

H40

B10

H30

English-French Package















H30













Japanese Package















B71Pro

B73

B74

B22

F72

WL15





K15







H30

F51

B11

H10R pro

H₃₀F

Chinese-English Package















B75-PVC color box

K15 PVC Gift box

B400 Gift box

Anti-Explosion Color box

Sales Box - S32









S32-J

S32-E

	Product	SKU	LED	Max	Max	Water	Size / Weight	Battery	Qty	ERP Code
lht	N S S S S S S S S S S S S S S S S S S S	B400	4*CREE XHP70B-N4	Brightness 12000LM	Run time	Resistance	152 × 64 × 54mm 426g	4*18650Power Li-ion Battery (3000mAh)	/Carton 0/6	284NBRL116
High performance Flashlight	ST. C.	B200	CREE XP-L HI V2	1000LM	12h	IP68	235 × 59 × 31mm 370g	2*18650 Li-ion Battery (2600mAh)	0/10	282NB101
rmance	The state of the s	B11	CREE XP-L HI V2	950LM	7h	IP67	80 × 28mm 80g	18350Li-ion Battery(1100mAh)	5/20	141BTRL9
th perfo	1 10	B60	CREE XP-L HI V2	1000LM	35h	IP68	154 × 41 × 28mm 166g	18650Li-ion Battery (3400mAh)	5/20	281NB103
H Oj	To the same of	B62	CREE XP-L HD V5	950LM	60h	IP67	128 × 28 × 26mm 80g	18650Li-ion Battery (2600mAh)	5/20	281NB302
	10	B75	SAMSUNG	1000LM	20h	IP65	160 × 28 mm 160g	18650Li-ion Battery (2600mAh)	5/20	281LRL907
	and the same	B70	OSRAM	1200LM	100h	IP65	160 × 26 mm 153g	18650Li-ion Battery (2600mAh)	5/20	281LL101
shlight		B71	SAMSUNG	1000LM	100h	IP67	126 × 27mm 153g	18650Li-ion Battery (2600mAh)	5/20	DL81010
Twist Flashlight	· ·	B74 Pro	SAMSUNG	700LM	7h	IP65	112 × 21 × 18mm 56g	USB-14500 Li-ion Battery (750mAh) /1*AA Battery	5/20	251LL103
90° Tv	The state of the s	B73	SAMSUNG	150LM	8h	IP65	152 × 18 × 15mm 51g	USB-10840 Li-ion Battery (600mAh) /2*AAA Battery	5/20	272LL305
		WL81	SAMSUNG	1000LM	10h	IP67	121 × 29mm 69g	18650 Li-ion Battery (2600mAh)	5/20	DX81010
	0.	WL15R	SEOUL LED COB	300LM 200LM	5h 8h	IPX4	164 × 22mm 80g	10840 Li-ion Battery inset (600mAh)	6/48	273WL302
۰	No.	EXB90	CREE XP-E2 R3	200LM	20h	IP65	160 × 35mm 175g	18650 Li-ion Battery (2200mAh)	5/20	EXB90
_	The state of the s	EXB701	CREE XP-E2R3	100LM	40h	IP64	160 × 28mm 153g	18650 Li-ion Battery (2600mAh)	5/20	EXB701
Anti-Explosion	-	EXH90	CREE XP-E2 R3	170LM	16h	IP65	60 × 51 × 50mm 88g	Li-ion Battery (1600mAh)	5/20	EXH90
		EXB93	CREE XP-G2 R5	250LM	16h	IP65	190 × 52mm 215g	18650 Li-ion Battery (2200mAh)	5/20	EXB93
		EXB91	CREELED	270LM	8h	IP68	120 × 23mm 91g	18650 Li-ion Battery (1900mAh)	5/20	EXB91
		EXB95	CREE LED	1000LM	16h	IP68	187 × 123 x 68mm 882g	18650 Li-ion Battery (2600mAh)	5/20	EXB95

Product	SKU	LED	Max Brightness	Max Run time	Water Resistance	Size / Weight	Battery	Qty /Carton	ERP Code	
	K15	CREELED	80LM	7h	IP65	75×16mm 17g	1*AAA Battery	6/36	171BM101	Chain Flashlight
-0	B10	CREE XP-E2R3	200LM	10h	IP65	65 × 20mm 19g	16340 Li-ion Battery (650mAh)	6/36	141ZRL102	hain Fla
	N1.1	CHINA 5MM LED	10LM	1h	IP65	36 × 11mm 4.2g	4*LR41 Battery	12/120	184XL102	Key-C
A STATE OF THE PARTY OF THE PAR	B24	LUMILEDS	150LM	1.5h	IP65	151 × 28mm 60g	10840 Li-ion Battery /2*AAA Battery	5/20	372NB304	Pen Light
	B22	LUMILEDS	120LM	2h	IP65	144 × 18mm 41g	2*AAA Battery	5/20	372NB201	Pen
	F81	CREE XPL-V5	1000LM	20h	IP65	163×35mm 156g	USB-18650 Li-ion Battery (2600mAh)	5/20	281NB201	Flashlight
	F51	CREE XP-L HD V5	600LM	5.5h	IPX4	103 × 26 × 20mm 55g	USB-14500 Li-ion Battery (750mAh) /1*AA Battery	5/20	351BL502	
	F72	SAMSUNG	140LM	2.5h	IP65	144×18mm 41g	2*AAA Battery	5/20	372NB208	Zoomable
Nagen (H17	COBLED	500LM	13h	IPX4	65 × 34 × 35mm 42g	14500 Li-ion Battery (800mAh)	5/20	151TRL6C	
MERCIN (S)	H11	SAMSUNG	500LM	11h	IP65	65 × 27.5 × 20.5mm 59g	USB-14500 Li-ion Battery (800mAh) /AABattery	5/20	151TRL6D	llamp
Trans	H35	SAMSUNG	1600LM	30h	IP65	78 × 41 × 43mm 58.5g	18650 Li-ion Battery (2600mAh)	5/20	181TRL9F01	Headlam
WIEB C	H10R	CREE XP-E2 R3	130LM	13h	IP65	92 × 24mm 65g	USB-14500 Li-ion Battery (750mAh) /AABattery	5/20	151NRL501	
4	H30	CREE XM-L2 U2	900LM	100h	IP68	78× 46× 44mm 166g	18650 Li-ion Battery (3400mAh)	/ 0/10	181TRL904	рв
4	H30F	CREE XM-L2 U2	900LM	5.5h	IP65	78 × 50 × 44mm 195g	18650 Li-ion Batter (3400mAh)	y 0/10	181TRL905	Belt and Road
Product	Batt	ery ERP Co	de Pro	duct	Batter	y ERP Code	Product	Battery	ERP Code	elt a
N1	1*AAA E	Battery 171N1	01	N4	2*AA Batt	ery 352GR101	N5	3*AAA Battery	373NL3	The B(
H40	3*AAA	Battery 70767	C	N61	USB-18 Li-ion Ba (2600m/	ttery 381NRL5	N63	USB-18650 Li-ion Battery (2600mAh)	381NRL5B	

Parameter Sheet 34